



Standard brake designed for 3/4" disc thickness

DISC DIAMETER	C/L FRICTION DIAMETER	MAX HUB DIAMETER	THRUSTER TYPE					
			ED23	ED30	ED50	ED80		
D1	D2	H1	W1	X1	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)
17.00	13.98	6.50	16.97	4.625	120 - 290	180 - 440	300 - 740	480 - 1210
17.75	14.73	7.25	17.35	5.000	120 - 300	180 - 460	310 - 780	510 - 1270
19.70	15.70	9.20	18.32	5.975	140 - 350	210 - 520	350 - 880	580 - 1440
21.00	17.00	10.50	18.97	6.625	150 - 370	220 - 560	380 - 950	620 - 1550
22.00	18.00	11.50	19.47	7.125	160 - 390	240 - 590	400 - 1010	660 - 1640
24.00	20.00	13.50	20.47	8.125	180 - 440	260 - 650	440 - 1110	720 - 1810
24.80	20.80	14.30	20.87	8.525	180 - 450	270 - 680	460 - 1150	750 - 1880
28.00	24.00	17.50	22.47	10.125	210 - 520	310 - 780	530 - 1320	860 - 2150
29.00	25.00	18.50	22.97	10.625	220 - 540	320 - 810	550 - 1380	900 - 2240
31.50	27.50	21.00	24.22	11.875	240 - 590	360 - 890	600 - 1510	980 - 2460

WGT (Lbs.) 194 204 224 226

All dimensions are shown in inches

PO Box 13615
Milwaukee, WI 53213
USA
Toll Free Phone: 800.288.8178
Toll Free Fax: 800.298.3503

N49 W13650 Campbell Drive
Menomonee Falls, WI 53051
USA
Phone: 262.783.3500
Fax: 262.783.3510

Canada Facility
2610 Dunwin Drive
Mississauga, Ontario
L5L 1J5 Canada
Toll Free Phone: 800.792.7253
Fax: 905.828.5707

www.magnetekmh.com