



Standard brake designed for 1.18" disc thickness

DISC DIAMETER	C/L FRICTION DIAMETER	MAX HUB DIAMETER	THRUSTER TYPE							
			ED30	ED50	ED80	ED121	ED201	ED301		
D1	D2	H1	W1	X1	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)	TORQUE (LbFt)
19.70	15.70	7.00	20.63	5.100	200 - 500	340 - 840	550 - 1380	840 - 2100	1320 - 3300	1880 - 4700
21.00	17.00	8.30	21.28	5.750	220 - 540	360 - 910	600 - 1490	910 - 2280	1440 - 3600	2040 - 5100
22.00	18.00	9.30	21.78	6.250	230 - 570	390 - 970	630 - 1580	970 - 2420	1520 - 3800	2160 - 5400
24.00	20.00	11.30	22.78	7.250	250 - 630	430 - 1080	700 - 1750	1070 - 2680	1680 - 4200	2400 - 6000
24.80	20.80	12.10	23.18	7.650	260 - 660	450 - 1120	730 - 1820	1120 - 2790	1760 - 4400	2520 - 6300
28.00	24.00	15.30	24.78	9.250	300 - 760	520 - 1290	840 - 2100	1280 - 3200	2040 - 5100	2880 - 7200
29.00	25.00	16.30	25.28	9.750	320 - 790	540 - 1340	880 - 2190	1360 - 3400	2120 - 5300	3000 - 7500
31.50	27.50	18.80	26.53	11.000	350 - 870	590 - 1480	960 - 2410	1480 - 3700	2320 - 5800	3320 - 8300
34.00	30.00	21.30	27.78	12.250	380 - 950	640 - 1610	1050 - 2630	1600 - 4000	2560 - 6400	3640 - 9100
35.40	31.40	22.70	28.48	12.950	400 - 990	680 - 1690	1100 - 2760	1680 - 4200	2680 - 6700	3800 - 9500
38.00	34.00	25.30	29.78	14.250	430 - 1070	730 - 1830	1190 - 2980	1840 - 4600	2880 - 7200	4120 - 10300
39.40	35.40	26.70	30.48	14.950	450 - 1120	760 - 1900	1240 - 3100	1880 - 4700	3000 - 7500	4280 - 10700
WGT (Lbs.)					425	445	447	480	480	482

All dimensions are shown in inches

PO Box 13615  
Milwaukee, WI 53213  
USA  
Toll Free Phone: 800.288.8178  
Toll Free Fax: 800.298.3503

N49 W13650 Campbell Drive  
Menomonee Falls, WI 53051  
USA  
Phone: 262.783.3500  
Fax: 262.783.3510

**Canada Facility**  
2610 Dunwin Drive  
Mississauga, Ontario  
L5L 1J5 Canada  
Toll Free Phone: 800.792.7253  
Fax: 905.828.5707

[www.magnetekmh.com](http://www.magnetekmh.com)