



@*	A	12"
**	B	16 1/2"
	C	13 1/8"
	D	13 1/8"
	E	8 1/2"
	F	15 5/8"
	G	14 3/8"
	H	9 3/4"
	I	8 13/16"
	J	2 1/4"
	L	1 3/4"
#*	M	9 3/4"
	N	1 1/8"
^	S	11 11/16"
	T	3/8"

FOR MORE INFO CONTACT:
American Crane & Equipment Corp.
Authorized Distributor
Tel: 877-503-2972
Fax: 484-945-0430
Email: sales@americancrane.com
www.americancrane.com

* TO WHEEL RUNNING SURFACE OF BEAM
 ** "B" APPLIES TO GEARED UNITS ONLY – FOR PLAIN UNITS DIM. "C" & "D" ARE MAX. 1/2 WIDTH
 @ FOR BEAMS WITH FLANGE THICKNESSES GREATER THAN 3/4" AT RUNNING SURFACE, "A" WILL INCREASE BY (FLANGE THICKNESS - 3/4")
 # TO UNDER BEAM ROLLER – (CLOSEST POINT OF CONTACT)
 ^ FROM THE FACE OF WHEEL TO END OF AXLE
 CUSTOMER MUST TAKE INTO CONSIDERATION FLANGE WIDTH AND THICKNESS OF BEAM

DIM. SHOWN ARE CORRECT FOR ANY "S" OR "W" BEAM, (FLAT TREAD WHEELS, NOT SHOWN, ARE SUPPLIED FOR "W" BEAM APPLICATIONS)

10&12 TON LOW HEADROOM HOIST

CHESTER HOIST
 LISBON, OHIO

DR. RLB	TR.	CK.	AP.
SCALE NONE		DATE 6-19-00	
REF. DWG. NO. ZLG-10T1 UPDATED			

Dwg. No. CD058

MK.	REVISIONS	CK-DATE
-----	-----------	---------