

WIRE ROPE GRIPS



Drop Forged Cable Clips

Size (in.)	Product Code	Min. no. clips	Rope turn-back (in.)	Torque† (ft.-lbs)	Weight per 100 (lbs)
1/8	M244	2	3-1/4	4-1/2	5
3/16	M245	2	3-3/4	7-1/2	9
1/4	M246	2	4-3/4	15	18
5/16	M247	2	5-1/4	30	30
3/8	M248	2	6-1/2	45	42
7/16	M249	2	7	65	70
1/2	M250	3	11-1/2	65	75
9/16	M296	3	12	95	100
5/8	M251	3	12	95	100
3/4	M252	4	18	130	150
7/8	M253	4	20	225	240
1	M254	5	26	225	250
1-1/8	M255	6	34	225	310
1-1/4	M256	7	37	360	460
1-3/8	M257	7	44	360	520
1-1/2	M258	8	48	360	590

- Precision manufactured and galvanized to meet Federal Specifications FF-C-450, Type 1, Class 1, on all sizes 1/4" and larger. U-bolts and nuts electro-galvanized on 1/8" and 3/16" sizes, hot dip galvanized all other sizes. All bases hot dip galvanized.
- Drop forged base.
- Available in popular sizes.
- 1/8"-5/8" sizes packed unassembled, two pieces per poly bag and in factory packs.
- 3/4" and larger sizes shipped assembled in factory packs.



Mid Grip Clips (Double Saddle)

Size (in.)	Product Code	Min. no. clips	Rope turn-back (in.)	Torque† (ft.-lbs)	Weight per 100 (lbs)
3/16 & 1/4	M2246	2	4	30	21
5/16	M2247	2	5	30	27
3/8	M2248	2	5-1/4	45	45
7/16	M2250	2	6-1/2	64	64
1/2	M2250	3	11	64	64
9/16	M2251	3	12-3/4	130	113
5/8	M2251	3	13-1/2	130	113
3/4	M2252	3	16	225	170

- Big Orange Mid-Grip wire rope clips meet Federal Specifications FF-C-450, Type III, Class 1, and will provide maximum holding strength when installed and used according to specifications.
- Double grip, double saddle wire rope allow full arc wrench swing for quicker installation, retightening or disassembly of nuts.
- Forged from special bar quality steel with the sizes clearly marked on the saddles.
- Furnished unassembled in poly bags and in factory packs of 20.

For more information contact:
American Crane & Equipment Corp.
Authorized Distributor
Tel: 877-503-2972
Fax: 484-945-0430
sales@americancrane.com
www.americancrane.com



PiggyBack Wedge Socket Clip

Size (in.)	Product Code	Weight each (lbs)	Torque† (ft.-lbs)
3/8	M248D	.8	45
7/16	M249D	1.3	65
1/2	M250D	1.4	65
9/16	M296D	1.7	95
5/8	M251D	1.7	95
3/4	M252D	2.5	130
7/8	M253D	3.6	225
1	M254D	3.9	225
1-1/8	M255D	4.9	225
1-1/4	M256D	6.5	360
1-3/8	M257D	7.1	360
1-1/2	M258D	8.2	360

- Attaches quickly and easily.
- Prevents load transfer to dead end rope.
- Eliminates need for short rope piece of loop on dead end.
- Properly secured dead end reduces possibility of snag/foul and shear off at wedge socket.
- Available in 3/8" to 1-1/2" sizes.
- Drop forged saddles.
- Application approved by OSHA.
- Hot dip galvanized, plus orange painted U-bolts.
- Patent 5,427,469 U.S. Class 403/396.

